THIS DRAWING IS PROPERTY OF "SUDHIR SYTTÓHGEARS PYT. LTD." AND MUST BE RETURNED ON REQUEST IT IS SUBMITED AS CONFIDENTIAL INFORMATION IN CONNECTION WITH ENCOURY, TENDER, ORDER, OR CONTRACTS IT IS NOT TO BE USED FOR ANY OTHER PURPOSE OR ORDER NOR MAY IT RE-COPIED OR LENT WITHOUT OUR AUTHORITY IN WRITING. FILE No. : DRAWING-2023/STD. G.A./JB104-1 6) 5) 7 4 3 2) Fitting OPTIONS: CABLE GLAND & PLUG VOLTAGE MATERIAL CONSTRUCTION CABLE ENTRIES AMP. RATING CANOPY PAINT SHADE CABLE ENTRY (LEFT SIDE) II II 2 Nos. ø8mm MOUNTING HOLES NAME PLATE FRONT VIEW LEFT / RIGHT / TOP / BOTTOM SIDE UPTO 30 Amp. (MAX.) M.S. / G.I. / FRP 632/355/7031/7032, etc... BRASS/S.S./ALUMINIUM STAINLESS STEEL WARNING 05 (CENTER DIST.) PLATE CUM 126 (BOTTOM SIDE) CABLE ENTRY \otimes (As per Standard) \oplus - EARTHING SCREW 55 (CENTER DIST.) ALL DIMENSIONS ARE IN MM UNLESS OTHERWISE SPECIFIED. CABLE ENTRY (RIGHT SIDE) æv. COMPONENT LAYOUT IS TENTATIVE RELOCATION OF PARTS & COMPONENTS OVERALL DIMENSIONS ARE ±10mm IS POSSIBLE AT THE TIME OF ACTUAL MANUFACTURING. NOTE : DATE CABLE DESCRIPTION SIDE VIEW TERMINALS 62 (III) DRN. 126 SHS. APPO SCALE N. T. S. REV.- 0 CHKD. APPD. 똞 JB/104-JB WODEL No.: JB/0A/104 Ŋ AKSHAY TEMPERATURE CLASS - T6 STOPPING PLUG -CABLE GLAND - (Ex d) DOUBLE COMPRESSION TYPE CABLE GLAND OF INTERNAL SIZE OF ENCLOSURE (BODY+COVER) - Ø80 x 40mm SR. NO., GAS GROUP, RATING, BIS MARKING, WARNING STATUS, etc....) S.S. NAME CUM WARNING PLATE (WITH DESCRIPTION TITLE, CIMFR, PESO MOUNTING ARRGT. - AS SHOWN IN DRG GASKET - NEOPRENE RUBBER GASKET HARDWARE - STAINLESS STEEL EARTHING - 1 No. INSIDE & 2 Nos. OUTSIDE M6 SIZE S.S./BRASS FINISH - INSIDE & OUTSIDE LIGHT GREY EPOXY POWDER COATING MATERIAL - CAST ALUMINIUM ALLOY INGRESS (IP) PROTECITON - IP:65, IS/IEC 60529 (2001) FLAMEPROOF (Ex d) PROTECITON - IIA/IIB, IS/IEC 60079-1 (2014) TERMINALS - MAX. 6 Nos. 2.5sq. mm CLIP-ON TYPE TERMINALS OF SCREWS WITH 2 Nos. PLAIN WASHER SHADE No. 631 AS PER IS:5 'CONNECTWELL/ELMEX' MAKE (DETAIL TO BE SPECIFIED BY CUSTOMER) Material / Components Specification : Reference IS/IEC Standard as follows : Standard Specification: 유 Dt. 28/05/2012 CMRI. CERT. No. CIMFR/TC/P/223 FLAMEPROOF-WEATHERPROOF ENCLOSURE FOR (Ex d) STOPPING PLUG OF 'SUDHIR' MAKE SUDHIR SWITCHGEARS PVT. LTD. 130. MUMBA SAMACHAR MARG, MUMBA - 400 023 JUNCTION BOX CM/L-0003931365 BIS LICENCE No.